

SC2000

Riding high on cleaning efficiency





Easy to control: Extremely user friendly and easy to learn. Dashboard with One-Touch button and intuitive display integrated in the steering wheel



Filling system with automatic shut off when tank is full (optional)



Easy to clean with recovery tank lid completely removable.

Micro ride-on scrubber dryer doubles productivity at price of walk-behind model

The Nilfisk SC2000 micro ride-on scrubber dryer eases the working effort significantly compared a walk-behind machine. An attractive choice for cleaning of offices, supermarkets, sports centers, shops, restaurants, hotels, and institutions like hospitals and schools.

Taking working speed up to 6 km/h – from an average 4 km/h with a walk-behind scrubber dryer– the SC2000 has a great impact on both productivity and cleaning costs. It is easy to maneuver even in narrow spaces thanks to its compact dimensions. Thanks to its silent mode function for ultra-low sound level, you can use the machine for daytime cleaning, even in sound sensitive areas.

Downtime is also minimized through the 2-key system: 1 grey key for the operator with basic setting and 1 yellow key for Superuser with full options setting to prevent any mistakes by the operator.

- Productive: High speed (6 km/h), 70/70 L tanks and 3.5 hours of running time
- Effective: 53 cm scrubbing width and powerful suction on all types of floors
- Consistent cleaning quality: Solution flow of detergent/ water automatically controlled by speed allowing consistency of cleaning result and saving water/detergent
- Powerful: Double pressure function to clean very dirty areas and whenever needed
- Low energy consumption: brush motor with speed control depending on floor condition
- User-friendly: Automatic deck and squeegee raising/ lifting by pressing the One-Touch button and Click on/off button to easily install and remove the brush/pad holder
- Easy handling: Light squeegee with patented elastic strap system to easily remove and change blades



Recovery tank fully tiltable gives easy access to battery compartment and Ecoflex system



USB port as optional



Reliability is also our mantra when it comes to service

A Nilfisk machine functions optimally when cared for by regular service and maintenance visits. Therefore we have created the optimal service solution: three levels of service reflecting different requirements and an optional supply of a substitute machine in critical situations.

Service Solutions Standard – Professional maintenance

Your contract encompasses two yearly maintenance visits and 48 hours response time. Breakdown visits and spare parts are billed separately.

Service Solutions Plus – Optimised performance

With the Plus solution you have a firm grip on your maintenance and repair costs while knowing that your performance is never compromised, only optimised.

Service Solutions Premium – Maximised uptime

If uptime is your absolute top priority and key concern, Service Solutions Premium is the best choice. A quarterly maintenance visit is included, and there are no sudden financial surprises.

Electric actuators for lowering/ raising the deck and the squeegee by pushing a



2 key system with separate setting controls for the Superuser and the Operator



Automatic squeegee lifting in reverse



Protective bumpers on brush deck and squeegee to absorb shocks.



Robust and chemical resistant polyethylene tanks



Easy access to operator's seat from both sides; ergonomic working position and foot pedal comfortably placed



Ecoflex system allows flexible detergent settings and water-only cleaning. 60-second burst of power to increase water, detergent and scrub pressure only when



Brush click-off/on button for easy installation and removal of brush/pad holder



Technical specifications

Description	Unit	SC2000	SC2000 Full package
Voltage	V	24	24
Rated power	W	450	450
Sound pressure level	dB(A)	68/62 ±3	68/62 ±3
Productivity rate theoretical/ actual	m ² /h	3180/2230	3180/2230
Scrubbing width	mm	530	530
Solution/recovery tank	litre	70/70	70/70
Brush/pad diameter	mm	530/508	530/508
Brush pressure	kg	15/30	15/30
Brush speed	rpm	155	155
Battery compartment size (lxwxh)	mm	350x360x280	350x360x280
Length x width x height	cm	127x55x102	127x55x102
Weight (machine only)	kg	155	228
Operating weight	kg	342	342
FEATURES:			
Squeezable drain hose with flow control		•	•
Debris cage		•	•
On-Board Charger		◦	•
Battery		◦	•
Ecoflex system		◦	•